



PTFE Tape 1x self-adhesive

Datum: 29-9-2025

Features

Sealing material made of 100% pure mono-expandable PTFE with a self-adhesive layer. Due to its one-sides structure, the tape will spread when tightened. The product has a wide range of applications due to its broad chemical resistance and wide temperature range.

Certification

- FDA 21 – FDA21CFR 177.500 (a) (1) u (b)
- BAM

Applications

It can be used as a flange seal in the same industrial applications as gaskets made from PTFE sheets.

The flanges can be made of steel, glass, plastic, etc.

Benefits

It is chemically resistant to almost all aggressive media and ensures a clean working environment. It is hydrophobic, age-resistant, UV-resistant, and has an unlimited lifespan. Quick and easy installation in most situations. On-site problem solving is possible. No gaskets need to be cut. Your needs can be met with several spools of tape of varying widths.



Technical Parameters.

Temperature range	-240°C - +270°C
pH	0 - 14

Standard Dimensions

• 3x2	• 5x2	• 7x2,5
• 10x3	• 12x4	• 14x5
• 17x6	• 20x7	• 22x5
• 25x5	• 28x5	• 40x5



Florijnstraat 6E
2988 CL, Ridderkerk
The Netherlands

T: +31 (0)180 762 609
E: info@teflontapes.nl
W: www.Teflontapes.nl